

NEW MIDDLE

VINYL WALLPAPERS


INSTABILELAB®
WALLCOVERING • TEXTILE • CARPETS



CHARACTERISTICS

DESCRIPTION: TNT BASE + PVC

COMPONENTS: CELLULOSE, SYNTHETIC FIBERS

GRAMMAGE: 380 g/m² (290 g/m² PVC, 90 g/m² PAPER)

INK: GREENGUARD GOLD CERTIFIED PRODUCT

REACTION TO FIRE: CLASS B-s2, d0

ROLL WIDTH: 68 cm

THICKNESS: min 0,31 mm - max 0,35 mm

INTENDED USE: RESIDENTIAL - COMMERCIAL - CONTRACT

WALLPAPER CLEANING

Vinyl wallcoverings can be cleaned with a damp cloth and a neutral detergent. Do not use abrasive sponges, alcohol or solvents.



APPLY ON SMOOTH SURFACES



GLUE INCLUDED



PRODUCT WASHABLE WITH WATER



RESISTANT TO LIGHT ABRASION



FOR INTERIOR WALLS AND CEILINGS

CERTIFICATIONS



EN 15102



REACTION TO FIRE CLASSE B-s2, d0



FREE OF VINYL CHLORIDE MONOMER, HEAVY METALS, LEAD, CADMIUM, EASILY VOLATILE PLASTICISERS AND CFC



INTERNATIONAL CERTIFICATION GUARANTEEING THE COMPANY'S COMMITMENT TO SUSTAINABLE PRODUCTION AND TO THE HEALTH AND SAFETY OF EMPLOYEES AND CONSUMERS



A+ VOC EMISSION
CERTIFIED



LOW CHEMICAL
EMISSION CERTIFIED



THE CERTIFIED
CHEMICAL IS SAFE

IMPORTANT INFO

ALL GRAPHICS OF THE COLLECTIONS EXCEPT 24K CAN BE PRINTED.

Make sure that the wall is suitable for the installation and completely smooth. Any irregularities or graininess must be removed from the surface so that the wallpaper adheres perfectly to the wall.



VIDEO INSTALLATION INSTRUCTIONS

