

MOQUETTE

TAPIS



MATÉRIAU PRESTIGIEUX AU POIL COURT ET CONFORTABLE, LA MOQUETTE EST L'ACCESSOIRE D'AMEUBLEMENT DANS LEQUEL LES MOTIFS, LES PAYSAGES ET LES NUANCES DES GRAPHISMES INSTABILELAB S'EXPRIMENT DANS L'ESPACE AVEC CARACTÈRE ET AVEC LA PLUS GRANDE LIBERTÉ DE PERSONNALISATION. C'EST CETTE LIBERTÉ QUI EN FAIT UN ÉLÉMENT UNIQUE DANS LE MONDE DE L'HÔTELLERIE, MAIS AUSSI UN CHOIX AUDACIEUX ET DÉCISIF DANS LES MAISONS QUI ACQUIÈRENT UN CHARME INTIME ET ÉTERNEL.

LA QUALITÉ DE CE MATÉRIAU RAFFINÉ AU TOUCHER ET À L'ŒIL OFFRE LA POSSIBILITÉ D'UN RENDU IMPECCABLE DU DESIGN CHOISI.

AMORTISSANT LES BRUITS ET FACILE À NETTOYER, LA MOQUETTE INSTABILELAB APORTE DE LA CHALEUR À TOUTE ATMOSPHÈRE EN S'ADAPTANT ET EN TRANSFORMANT TOUT ESPACE. UN COMPLÉMENT CAPABLE DE FAIRE LA DIFFÉRENCE ENTRE UN ENVIRONNEMENT IMPECCABLE ET UN ENVIRONNEMENT INOUBLIABLE.

DIMENSIONS



TECHNICAL DETAILS

MANUFACTURING PROCESS	DIN ISO 2424	TUFTED 1/10"
FRONTSIDE STRUCTURE	DIN ISO 2424	CUT PILE - SAXONY
COLOR	DIN ISO 2424	CHROMOJET PRINT
PILE MATERIAL		100 % POLYAMID PA 6
PRIMARY BACKING	DIN ISO 2424	PES WOVEN
SECONDARY BACKING	DIN ISO 2424	ACTION BACK
PILE WEIGHT	DIN ISO 2424	Approx. 1050 g/m ²
TOTAL WEIGHT	ISO 8543	Approx. 2222 g/m ²
PILE HEIGHT	ISO 1766	Approx. 5,5 mm
TOTAL THICKNESS	ISO 1765	Approx. 6,8 mm
NUMBER OF KNOTS	ISO 1763	Approx. 213000/m ²
WIDTH	DIN 3018	Approx. 400 cm

FUNCTIONAL PROPERTIES

WEAR CLASSIFICATION	EN 1307:2019	23/32
COMFORT RATING	EN 1307:2019	LC 3
CASTOR CHAIR RESTISTANCE	EN 985:Prüfung A	CLASS A

PHYSICAL PROPERTIES

FIRE RATING	DIN EN 13501-1	Cfl-s1 *1
-------------	----------------	-----------

FASTNESSES

COLOUR FASTNESS TO LIGHT	EN ISO 105-B02:2013	6-7
COLOUR FASTNESS TO WATER	DIN EN ISO 105 E01:2013	5
RUBBERING FASTNESS DRY/WET	DIN EN ISO 105 X12:2002	5/5

FOND DE LA MOQUETTE



Fond structuré de la moquette.



FOR AREAS WITH INTENSIVE USE (HEAVY)



FOR AREAS WITH NORMAL COMMERCIAL USE



FLAME RETARDANT C_{fl}-s1



PERMANENT USE



LUXURY CLASS LC3



CE MARKING



EUROFINS INDOOR AIR COMFORT (GOLD)

